

CREATEC AND STYLELITE HIGH GLOSS DOORS & PANELS

DO	DO NOT
✓ Use a clean, damp microfiber cloth or soft cloth or chamois	✗ Use paper towel, brushes, scourers or scrapers
✓ Use mild washing detergent	✗ Use abrasive cleaners
✓ Remove streaks with a good quality glass cleaner	✗ Use Thinners or Methylated Spirits

STYLELITE

- Do not dry wipe at any time

The StyleLite surface becomes more scratch resistant over the first few days after the protective film has been removed.

This process can be accelerated by lightly polishing immediately using Novus No 1. Or Plexus plastic polishes with a clean microfiber cloth.

General cleaning

Apply Novus No 1. Plastic Polish, Plexus Plastic Polish or warm soapy water and wipe using a clean microfiber, soft cloth or damp chamois.

Removing Marks and Light Scratches

Apply Novus No 2. or a good quality liquid polish (eg. 3M Finesse-It II) and using a damp, clean microfiber or soft cloth. Polish in a circular pattern. Remove polish using General Cleaning procedure above.

Removing Heavier Scratches

Apply Novus No 3. or a good quality fine compound polish (eg. 3M Perfect-It III) and using a damp, clean microfiber or soft cloth. Polish in a back and forth motion at right angles to the visible scratches. Then use Removing Marks and Light Scratches procedure, then General Cleaning procedure above.

Ensure all polish residue is removed completely from the StyleLite surface. Low speed electric buffing can also be used to repair marks and scratches.

CREATEC

- Use rangehoods whenever cooking, to avoid steam and cooking oil vapours from adversely affecting surfaces.

To ensure that your polytec limited 7 year warranty will not be void:

DO NOT use any of the following on polytec CREATEC doors and panels:

Commercial Cleaning Products, Abrasive Cleaners, Scouring Pads or Abrasive Papers, Acids or Alkalis, Solvents, Thinners, Turpentine, Ammonia, Bleach, Acetone, Easy-Off BAM!, M.E.K. or any other cleaning agents containing organic solvents